

Port Sections Guide

Port of Rotterdam



6-12-2016

Section	1e Petroleumhaven duoy - dolphin 51
Check Section	Check 1e Petroleumhaven
Photo/Chart	58


Position (lat / lon)	51°52' 9N 004°20' 9E
UKC policy alongside	See basin
Tidal range	See basin
Range of water densities	See basin
Bottom type	See basin
Dredging regime	N/A
Free text	Petroleum harbour safety regime. STS only in barges with vapour return line. STS + bunkering on west side of vessel. No sea-going vessel alongside. Only closed tank cleaning. Cleaning operations only after consulting HCC.

Manoeuvre Arrival

UKC policy	See basin
Size restriction	Max. loa 120 meters. Distance buoy - dolphin 160 meters.
Tidal restriction	See basin
Wind restriction	For one vessel: Bft 6 (13,8 m/s), from 45 till 135 degrees from the port/starboard bow For two vessel: Bft 5 (10,7 m/s), from 45 till 135 degrees from the port/starboard bow If wind speed limits are exceeded: sufficient tugs in the side or shift to berth or sea. Wind speeds are measured on board the vessel.
Visibility restriction	N/A
Speed restriction	N/A
Passing requirements	N/A
Tug use	See basin
Berthing requirements	The vessel should moor with her bow heading into the wind and make use of a minimum of 1 anchor if possible, to be dropped on windward side. Position the stern closer to the buoys than the bow. Sufficient tension on lines to submerge buoy halfway. At night switch on deck lights to show the outline of the vessel. No double banking with seagoing vessels.
Free text option	N/A

Manoeuvre Departure

UKC policy	See basin
Size restriction	See arrival
Tidal restriction	See basin
Wind restriction	See arrival
Visibility restriction	N/A
Speed restriction	N/A
Passing requirements	N/A
Tug use	N/A
Unberthing requirements	N/A



Port Sections Guide



Port of Rotterdam

6-12-2016

Section	1e Petroleumhaven duoy - dolphin 51
Check Section	Check 1e Petroleumhaven
Photo/Chart	58
Free text option	N/A