



Port Sections Guide

Port of Rotterdam



21-4-2020

Section	Waalhaven Buoy/Dolphin 23
Check	Check Waalhaven
Photo/Chart	69

Position (lat / lon)	51°53'.64N 004°26'.7E
UKC policy alongside	See basin
Tidal range	See basin
Range of water densities	See basin
Bottom type	See basin
Dredging regime	N/A
Free text	Break bulk regime. Zone D. STS tankers conform HVR 2020 art 5.5, 5.6, 5.7. and 6.2, 6.3. STS mineral oils not allowed. Bunkering via barge on both sides of the vessel. Cargo operations on both sides when enough space available and buoy 20-21 and 25 are free.

Manoeuvre Arrival

UKC policy	See basin
Size restriction	Max. loa 165 meters. Distance between buoy and dolphin are 215 meter.
Tidal restriction	See basin
Wind restriction	For one vessel: Bft 6 (13,8 m/s), from 45 till 135 degrees from the port/starboard bow For two vessel: Bft 5 (10,7 m/s), from 45 till 135 degrees from the port/starboard bow If wind speed limits are exceeded: sufficient tugs in the side or shift to berth or sea. Wind speeds are measured on board the vessel
Visibility restriction	N/A
Speed restriction	N/A
Passing requirements	See basin
Tug use	See basin
Berthing requirements	The vessel should moor with her bow heading West due to limited room to buoy span 24 Anchor to be dropped on windward side. Sufficient tension on lines to submerge buoy halfway. At night switch on deck lights to show the outline of the vessel.
Free text option	N/A

Manoeuvre Departure

UKC policy	See basin
Size restriction	See arrival
Tidal restriction	See basin
Wind restriction	See arrival
Visibility restriction	N/A
Speed restriction	N/A
Passing requirements	See basin
Tug use	See basin
Unberthing requirements	N/A
Free text option	N/A